



**REFERENCES**

## REFERENCES

- [1] Kim, H. T. and Han, Y. H. (2004). Sintering of nanocrystalline BaTiO<sub>3</sub>. **Ceramics International**, 30, 1719-1723.
- [2] Yoshimura, M., Suchanek, W. L., Watanabe, T. and Sakurai, B. (1999). In situ fabrication of SrTiO<sub>3</sub>-BaTiO<sub>3</sub> layered thin films by hydrothermal-electrochemical technique. **Journal of the European Ceramic Society**, 19, 1353-1359.
- [3] Koerfer, S., De Souza, R. A., Yoo, H.I. and Martin, M. (2008). Diffusion of Sr and Zr in BaTiO<sub>3</sub> single crystals. **Solid State Sciences**, 10, 725-734.
- [4] Pantou, R., Dubourdieu, C., Weiss, F., Kreisel, J., Köbernik, G. and Haessler, W. (2002). Effect of substitution of Ti by Zr in BaTiO<sub>3</sub> thin films grown by MOCVD. **Materials Science in Semiconductor Processing**, 5, 237-241.
- [5] Ciomaga, C.E., Calderone, R., Buscaglia, M.T., Viviani, M., Buscaglia, V., Mitoseriu, L., Stancu, A. and Nanni, P. (2006) Relaxor properties of Ba(Zr,Ti)O<sub>3</sub> ceramics. **J. Optoelectron. Adv. Mater**, 8, 944-948.
- [6] Chen, H., Yang, C., Fu, C., Shi, J., Zhang, J. and Leng, W. (2008). Microstructure and dielectric properties of BaZr<sub>x</sub>Ti<sub>1-x</sub>O<sub>3</sub> ceramics. **J. Mater. Sci.**, 19, 379-382.
- [7] Reddy, S. B., Rao, K. P. and Rao, M. S. R. (2007). Nanocrystalline barium zirconate titanate synthesized at low temperature by an aqueous co-precipitation technique. **Scripta Materialia**, 57, 591-594.
- [8] Kuang, S. J., Tang, X. G., Li, L. Y., Jiang, Y. P. and Liu, Q. X. (2009). Influence of Zr dopant on the dielectric properties and Curie temperatures of Ba(Zr<sub>x</sub>Ti<sub>1-x</sub>)O<sub>3</sub> (0 ≤ x ≤ 0.12) ceramics. **Scripta Materialia**, 61, 68-71.
- [9] Binhayeeniyi, N., Sukvisut, P., Thanachayanont, C. and Muensit, S. (2010). Physical and electromechanical properties of barium zirconium titanate synthesized at low-sintering temperature. **Materials Letters**, 64, 305-308
- [10] Nanakorn, N., Jalupoom, P., Vaneesorn, N. and Thanaboonsombut, A. (2008). Dielectric and ferroelectric properties of Ba(Zr<sub>x</sub>Ti<sub>1-x</sub>)O<sub>3</sub> ceramics. **Ceramics International**, 34, 779-782.

- [11] Razak, K. A., Yip, C. J. and Sreekantan, S. (2011). Synthesis of  $(\text{Bi}_{0.5}\text{Na}_{0.5})\text{TiO}_3$  (BNT) and Pr doped BNT using the soft combustion technique and its properties. **Journal of Alloys and Compounds**, 509, 2936-2941.
- [12] Lu, W., Wang, Y., Fan, G., Wang, X. and Liang, F. (2011). The structural and electric properties of Li- and K-substituted  $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$  ferroelectric ceramics. **Journal of Alloys and Compounds**, 509, 2738-2744.
- [13] Choy, S. H. and Chan, H. L. W. (2011). Nonlinear behavior of BNT-based lead-free piezoceramics under various ac fields. **Current Applied Physics**, 11, 869-877.
- [14] Naderer, M., Schütz, D., Kainz, T., Reichmann, K. and Mittermayr, F. (2012). The formation of secondary phases in  $\text{Bi}_{0.5}\text{Na}_{0.375}\text{K}_{0.125}\text{TiO}_3$  ceramics. **Journal of the European Ceramic Society**, 32, 2399-2404.
- [15] Li, H., Feng, C. and Yao, W. (2004). Some effects of different additives on dielectric and piezoelectric properties of  $(\text{Bi}_{1/2}\text{Na}_{1/2})\text{TiO}_3$ - $\text{BaTiO}_3$  morphotropic-phase-boundary composition. **Materials Letters**, 58, 1194-1198.
- [16] Laoratanakul, P., Yimnirun, R. and Wongsanmai, S. (2011). Phase formation and dielectric properties of bismuth sodium titanate-potassium sodium niobate ceramics. **Current Applied Physics**, 11, S161-S166.
- [17] Du, P., Luo, L., Li, W., Zhang, Y. and Chen, H. (2013). Photoluminescence and piezoelectric properties of Pr-doped NBT- $x$ BZT ceramics: Sensitive to structure transition. **Journal of Alloys and Compounds**, 559, 92-96.
- [18] Lee, W., Lee, M., Tseng, C., Huang, Y. and Wu, C. (2009). Crystal structure and ferroelectric properties of  $(\text{Bi}_{0.5}\text{Na}_{0.5})\text{TiO}_3$ - $\text{Ba}(\text{Zr}_{0.05}\text{Ti}_{0.95})\text{O}_3$  piezoelectric ceramics. **Journal of the American Ceramic Society**, 92, 1069-1073.
- [19] Parija, B., Badapanda, T., Rout, S. K., Cavalcante, L. S., Panigrahi, S., Longo, E., et al. (2013). Morphotropic phase boundary and electrical properties of  $1-x[\text{Bi}_{0.5}\text{Na}_{0.5}]\text{TiO}_3$ - $x\text{Ba}[\text{Zr}_{0.25}\text{Ti}_{0.75}]\text{O}_3$  lead-free piezoelectric ceramics. **Ceramics International**, 39, 4877-4886.
- [20] Hwang, C.-C., Wu, T.-Y., Wan, J. and Tsai, J.-S. (2004). Development of a novel combustion synthesis method for synthesizing of ceramic oxide powders. **Materials Science and Engineering: B**, 111, 49-56.



- [21] Mangalaraja, R. V., Mouzon, J., Hedström, P., Kero, I., Ramam, K. V. S., Camurri, C. P., et al. (2008). Combustion synthesis of  $Y_2O_3$  and  $Yb-Y_2O_3$ : Part I. Nanopowders and their characterization. **Journal of Materials Processing Technology**, 208, 415-422.
- [22] Xu, J., Xue, D. and Yan, C. (2005). Chemical synthesis of  $NaTaO_3$  powder at low-temperature. **Materials Letters**, 59, 2920-2922.
- [23] George, C. N., Thomas, J. K., Kumar, H. P., Suresh, M. K., Kumar, V. R., Wariar, P. R. S., et al. (2009). Characterization, sintering and dielectric properties of nanocrystalline barium titanate synthesized through a modified combustion process. **Materials Characterization**, 60, 322-326.
- [24] Feng, Q., Ma, X. H., Yan, Q. Z. and Ge, C. C. (2009). Preparation of soft-agglomerated nano-sized ceramic powders by sol-gel combustion process. **Materials Science and Engineering: B**, 162, 53-58.
- [25] Moulson, A. J. and Herbert, J. M. (1992). **Electroceramics**. London: Chapman & Hall.
- [26] Barsoum, M. W. (2003). **Fundamentals of ceramics**. London: McGraw-Hill.
- [27] Haertling, G. H. (1999). Ferroelectric ceramics: history and technology. **J. Am. Ceram. Soc.**, 82, 797-818.
- [28] Safari, A., Panda, R. K. and Janas, V. F. (1996). Lead-free materials. **Key Engineering Materials**, 122, 35-70.
- [29] Loehman, R. E. (2010). **Characterization of ceramics**. New York: Taylor&Francis.
- [30] Dixit, A., Majumder, S. B., Dobal, P. S., Katiyar, R. S. and Bhalla, A. S. (2004). Phase transition studies of sol-gel deposited barium zirconate titanate thin films. **Thin Solid Films**, 447-448, 284-288.
- [31] Huang, H.H., Chiu, H.H.S., Wu, N.C. and Wang, M.C. (2008). Tetragonality and properties of  $Ba(Zr_xTi_{1-x})O_3$  ceramics determined using the Rietveld method. **Metallurgical and Materials Transactions**, 39A, 3276-3284.
- [32] Neirman, S. M. (1988). The Curie point temperature of  $Ba(Zr_xTi_{1-x})O_3$  solid solutions. **Journal of Materials Science**, 23, 3973-3980.

- [33] Moura, F., Simões, A. Z., Stojanovic, B. D., Zaghet, M. A., Longo, E. and Varela, J. A. (2008). Dielectric and ferroelectric characteristics of barium zirconate titanate ceramics prepared from mixed oxide method. **Journal of Alloys and Compounds**, 462, 129-134.
- [34] Yu, Z., Ang, C., Guo, R. and Bhalla, A. S. (2007). Dielectric properties of  $\text{Ba}(\text{Zr}_x\text{Ti}_{1-x})\text{O}_3$  solid solutions. **Materials Letters**, 61, 326-329.
- [35] Xiong, J.W., Zeng, B. and Cao, W.Q. (2008). Investigation of dielectric and relaxor ferroelectric properties in  $\text{Ba}(\text{Zr}_x\text{Ti}_{1-x})\text{O}_3$  ceramics. **Journal of Electroceramics**, 21, 124-127.
- [36] Jaita, P., Watcharapasorn, A. and Jiansirisomboon, S. (2011). Effects BNT compound incorporated on structure and electrical properties of PZT ceramic. **Current Applied Physics**, 11, S77-S81.
- [37] Hiruma, Y., Yoshii, K., Nagata, H. and Takenaka, T. (2008). Phase transition temperature and electrical properties of  $(\text{Bi}_{1/2}\text{Na}_{1/2})\text{TiO}_3-(\text{Bi}_{1/2}\text{A}_{1/2})\text{TiO}_3$  (A= Li and K) lead-free ferroelectric ceramics. **Journal of Applied Physics**, 103, 084121.
- [38] Pookmanee, P., Rujijanagul, G., Ananta, S., Heimann, R. B. and Phanichphant, S. (2004). Effect of sintering temperature on microstructure of hydrothermally prepared bismuth sodium titanate ceramics. **Journal of the European Ceramic Society**, 24(2), 517-520.
- [39] Ji, W.-J., Chen, Y.-B., Zhang, S.-T., Yang, B., Zhao, X.-N. and Wang, Q.-J. (2012). Microstructure and electric properties of lead-free  $0.8\text{Bi}_{1/2}\text{Na}_{1/2}\text{TiO}_3-0.2\text{Bi}_{1/2}\text{K}_{1/2}\text{TiO}_3$  ceramics. **Ceramics International**, 38, 1683-1686.
- [40] Chou, C.-S., Wu, C.-Y., Yang, R.-Y. and Ho, C.-Y. (2012). Preparation and characterization of the bismuth sodium titanate ( $\text{Na}_{0.5}\text{Bi}_{0.5}\text{TiO}_3$ ) ceramic doped with ZnO. **Advanced Powder Technology**, 23, 358-365.
- [41] Hiruma, Y., Nagata, H. and Takenaka, T. (2009). Depolarization temperature and piezoelectric properties of  $(\text{Bi}_{1/2}\text{Na}_{1/2})\text{TiO}_3-(\text{Bi}_{1/2}\text{Li}_{1/2})\text{TiO}_3-(\text{Bi}_{1/2}\text{K}_{1/2})\text{TiO}_3$  lead-free piezoelectric ceramics. **Ceramics International**, 35, 117-120.



- [42] Yang, Z., Liu, B., Wei, L. and Hou, Y. (2008). Structure and electrical properties of  $(1-x)\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3-x\text{Bi}_{0.5}\text{K}_{0.5}\text{TiO}_3$  ceramics near morphotropic phase boundary. **Materials Research Bulletin**, 43, 81-89.
- [43] Chu, B.-J., Chen, D.-R., Li, G.-R. and Yin, Q.-R. (2002). Electrical properties of  $\text{Na}_{1/2}\text{Bi}_{1/2}\text{TiO}_3\text{-BaTiO}_3$  ceramics. **Journal of the European Ceramic Society**, 22, 2115-2121.
- [44] Peng, C., Li, J.-F. and Gong, W. (2005). Preparation and properties of  $(\text{Bi}_{1/2}\text{Na}_{1/2})\text{TiO}_3\text{-Ba}(\text{Ti,Zr})\text{O}_3$  lead-free piezoelectric ceramics. **Materials Letters**, 59, 1576-1580.
- [45] Eichelbaum, M., Farrauto, R. J. and Castaldi, M. J. (2010). The impact of urea on the performance of metal exchanged zeolites for the selective catalytic reduction of NO<sub>x</sub>: Part I. Pyrolysis and hydrolysis of urea over zeolite catalysts. **Applied Catalysis B: Environmental**, 97, 90-97.
- [46] Chaiyo, N., Muanghlua, R., Niemcharoen, S., Boonchom, B. and Vittayakorn, N. (2011). Solution combustion synthesis and characterization of lead-free piezoelectric sodium niobate ( $\text{NaNbO}_3$ ) powders. **Journal of Alloys and Compounds**, 509, 2445-2449.
- [47] Pampuch, R. (1999). Advanced HT ceramic materials via solid combustion. **Journal of the European Ceramic Society**, 19, 2395-2404.
- [48] Fumo, D. A., Jurado, J., Segadães, A. M. and Frade, J. R. (1997). Combustion synthesis of iron-substituted strontium titanate perovskites. **Materials Research Bulletin**, 32, 1459-1470.
- [49] Chavan, S. V., Pillai, K. T. and Tyagi, A. K. (2006). Combustion synthesis of nanocrystalline yttria: Tailoring of powder properties. **Materials Science and Engineering: B**, 132, 266-271.
- [50] Fumo, D. A., Morelli, M. R. and Segadães, A. M. (1996). Combustion synthesis of calcium aluminates. **Materials Research Bulletin**, 31, 1243-1255.
- [51] Madhana Kumar, K. S. and John Berchmans, L. (2009). Combustion synthesis of copper doped calcium aluminate. **Ceramics International**, 35, 1277-1280.

- [52] Thongtha, A. and Bongkarn, T. (2009). Phase formation and microstructure of barium zirconate ceramics prepared using the combustion technique. **Ferroelectrics**, 383, 33-39.
- [53] Panya, P. and Bongkarn, T. (2009). Fabrication of perovskite barium titanate ceramics using combustion route. **Ferroelectrics**, 383, 102-110.
- [54] Thongtha, A. and Bongkarn, T. (2010). Fabrication and characterization of perovskite SrZrO<sub>3</sub> ceramics through a combustion technique. **Key Engineering Materials**, 421-422, 223-226.
- [55] Phungjitt, N., Panya, P., Bongkarn, T. and Vittayakorn, N. (2009). The structure phase and microstructures of perovskite Ba(Ti<sub>1-x</sub>Zr<sub>x</sub>)O<sub>3</sub> ceramics using the combustion route. **Func. Matter. Lett.**, 4, 169-174.
- [56] Tian, Z., Lin, L., Meng, F. and Huang, W. (2009). Combustion synthesis and characterization of nanocrystalline Ba(Mg<sub>1/3</sub>Nb<sub>2/3</sub>)O<sub>3</sub> powders. **Mat. Sci. Eng. B-Solid**, 158, 188-191.
- [57] Sittiketkorn, P., Ramaneepikool, S. and Bongkarn, T. (2010). The effects of firing temperatures on phase formation and microstructure of Pb<sub>0.975</sub>Sr<sub>0.025</sub>TiO<sub>3</sub> ceramics synthesized via the combustion technique. **Ferroelectrics**, 403, 158-165.
- [58] Sumang, R. and Bongkarn, T. (2010). The effect of excess PbO on crystal structure, microstructure, phase transition and dielectric properties of (Pb<sub>0.75</sub>Sr<sub>0.25</sub>)TiO<sub>3</sub> ceramics. **Ferroelectrics**, 403, 82-90.
- [59] Maison, W., Kleeberg, R., Heimann, R. B. and Phanichphant, S. (2003). Phase content, tetragonality, and crystallite size of nanoscaled barium titanate synthesized by the catecholate process: effect of calcination temperature. **Journal of the European Ceramic Society**, 23, 127-132.
- [60] Thongtha, A., Angsukased, K. and Bongkarn, T. (2010). Influences of firing temperatures on phase and morphology evolution of (Ba<sub>0.25</sub>Sr<sub>0.75</sub>)(Zr<sub>0.75</sub>Ti<sub>0.25</sub>)O<sub>3</sub> ceramics synthesized via solid-state reaction method. **Key Engineering Materials**, 421-422, 247-250.



- [61] Eitssayeam, S., Intatha, U., Pengpat, K., Rujijanagul, G., MacKenzie, K. J. D. and Tunkasiri, T. (2009). Effect of the solid-state synthesis parameters on the physical and electronic properties of perovskite-type  $\text{Ba}(\text{Fe,Nb})_{0.5}\text{O}_3$  ceramics. **Current Applied Physics**, 9(5), 993-996.
- [62] Chen, C.-Y., Hu, Y., Lin, H.-L. and Wei, W.-Y. (2007). Influence of the sintering temperature on phase development in PMnN–PZT ceramics. **Ceramics International**, 33(2), 263-268.
- [63] Chiang, Y.M., Birnle, D.P. and Kingery, W.D. (1997). **Physical Ceramics: Principle for ceramics science and engineer**. Canada: John Wiley & Sons.
- [64] German, R.M. (1996). **Sintering theory and practice**. Canada: John Wiley & Sons.
- [65] Ricinschi, D., Ciomaga, C. E., Mitoseriu, L., Buscaglia, V. and Okuyama, M. (2010). Ferroelectric–relaxor crossover characteristics in  $\text{Ba}(\text{Zr}_x\text{Ti}_{1-x})\text{O}_3$  ceramics investigated by AFM-piezoresponse study. **Journal of the European Ceramic Society**, 30(2), 237-241.
- [66] Julphunthong, P. and Bongkarn, T. (2011). Phase formation, microstructure and dielectric properties of  $\text{Ba}(\text{Zr}_{0.1}\text{Ti}_{0.9})\text{O}_3$  ceramics prepared via the combustion technique. **Current Applied Physics**, 11, S60-S65.
- [67] Tang, X. G., Chew, K. H. and Chan, H. L. W. (2004). Diffuse phase transition and dielectric tunability of  $\text{Ba}(\text{Zr}_y\text{Ti}_{1-y})\text{O}_3$  relaxor ferroelectric ceramics. **Acta Materialia**, 52, 5177-5183.
- [68] Zuo, R., Su, S., Wu, Y., Fu, J., Wang, M. and Li, L. (2008). Influence of A-site nonstoichiometry on sintering, microstructure and electrical properties of  $(\text{Bi}_{0.5}\text{Na}_{0.5})\text{TiO}_3$  ceramics. **Materials Chemistry and Physics**, 110, 311-315.
- [69] Choy, S. H. and Chan, H. L. W. (2011). Nonlinear behavior of BNT-based lead-free piezoceramics under various ac fields. **Current Applied Physics**, 11, 869-877.
- [70] Yang, Z., Liu, B., Wei, L. and Hou, Y. (2008). Structure and electrical properties of  $(1-x)\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3-x\text{Bi}_{0.5}\text{K}_{0.5}\text{TiO}_3$  ceramics near morphotropic phase boundary. **Materials Research Bulletin**, 43, 81-89.



- [71] Zuo, R., Su, S., Wu, Y., Fu, J., Wang, M. and Li, L. (2008). Influence of A-site nonstoichiometry on sintering, microstructure and electrical properties of  $(\text{Bi}_{0.5}\text{Na}_{0.5})\text{TiO}_3$  ceramics. **Materials Chemistry and Physics**, 110, 311-315.
- [72] Zhang, Y., Zheng, X. and Zhang, T. (2011). Characterization and humidity sensing properties of  $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3\text{-Bi}_{0.5}\text{K}_{0.5}\text{TiO}_3$  powder synthesized by metal-organic decomposition. **Sensors and Actuators B: Chemical**, 156, 887-892.
- [73] Liao, Y., Xiao, D., Lin, D., Zhu, J., Yu, P., Wu, L., et al. (2007). Synthesis and properties of  $\text{Bi}_{0.5}(\text{Na}_{1-x-y}\text{K}_x\text{Ag}_y)_{0.5}\text{TiO}_3$  lead-free piezoelectric ceramics. **Ceramics International**, 33, 1445-1448.
- [74] Naderer, M., Schütz, D., Kainz, T., Reichmann, K. and Mittermayr, F. (2012). The formation of secondary phases in  $\text{Bi}_{0.5}\text{Na}_{0.375}\text{K}_{0.125}\text{TiO}_3$  ceramics. **Journal of the European Ceramic Society**, 32(10), 2399-2404.
- [75] Lin, D., Kwok, K. W. and Chan, H. L. W. (2008). Structure and electrical properties of  $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3\text{-BaTiO}_3\text{-Bi}_{0.5}\text{Li}_{0.5}\text{TiO}_3$  lead-free piezoelectric ceramics. **Solid State Ionics**, 178, 1930-1937.
- [76] Choy, S. H. and Chan, H. L. W. (2011). Nonlinear behavior of BNT-based lead-free piezoceramics under various ac fields. **Current Applied Physics**, 11, 869-877.
- [77] Hou, Y., Hou, L., Zhu, M., Wang, H. and Yan, H. (2007). Sol-gel synthesis of lead-free  $(\text{K}_{0.5}\text{Bi}_{0.5})_{0.4}\text{Ba}_{0.6}\text{TiO}_3$  nanorods. **Materials Letters**, 61, 3371-3373.
- [78] Liu, Y., Lu, Y. and Dai, S. (2009). Hydrothermal synthesis of monosized  $\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$  spherical particles under low alkaline solution concentration. **Journal of Alloys and Compounds**, 484, 801-805.
- [79] Chen, W., Kume, S. and Watari, K. (2005). Molten salt synthesis of  $0.94(\text{Na}_{1/2}\text{Bi}_{1/2})\text{TiO}_3\text{-}0.06\text{BaTiO}_3$  powder. **Materials Letters**, 59, 3238-3240.
- [80] Zhou, F., Xu, Y., Li, D. and Wang, T. (1989).  $(\text{Na}_{0.5}\text{Bi}_{0.5})\text{TiO}_3$ : Synthesis and X-Ray Powder Diffraction Data. **Powder diffraction**, 4, 223-225.

- [81] König, J., Spreitzer, M., Jančar, B., Suvorov, D., Samardžija, Z. and Popovič, A. (2009). The thermal decomposition of  $K_{0.5}Bi_{0.5}TiO_3$  ceramics. **Journal of the European Ceramic Society**, 29, 1695-1701.
- [82] Yang, Z., Hou, Y., Pan, H. and Chang, Y. (2009). Structure, microstructure and electrical properties of  $(1-x-y)Bi_{0.5}Na_{0.5}TiO_3-xBi_{0.5}K_{0.5}TiO_3-yBi_{0.5}Li_{0.5}TiO_3$  lead-free piezoelectric ceramics. **Journal of Alloys and Compounds**, 480, 246-253.
- [83] Yuan, Y., Zhang, S.R., Zhou, X.H., Tang, B. and Li, B. (2009). High-temperature capacitor materials based on modified  $BaTiO_3$ . **Journal of Electronic materials**, 38, 706-710.
- [84] Wada, N., Hiramatsu, T., Tamura, T. and Sakabe, Y. (2008). Investigation of grain boundaries influence on dielectric properties in fine-grained  $BaTiO_3$  ceramics without the core-shell structure. **Ceramics International**, 34, 933-937.
- [85] Zhou, C., Liu, X., Li, W. and Yuan, C. (2009). Structure and piezoelectric properties of  $Bi_{0.5}Na_{0.5}TiO_3-Bi_{0.5}K_{0.5}TiO_3-BiFeO_3$  lead-free piezoelectric ceramics. **Materials Chemistry and Physics**, 114, 832-836.
- [86] Zou, M., Fan, H., Chen, L. and Yang, W. (2010). Microstructure and electrical properties of  $(1-x)[0.82Bi_{0.5}Na_{0.5}TiO_3-0.18Bi_{0.5}K_{0.5}TiO_3]-xBiFeO_3$  lead-free piezoelectric ceramics. **Journal of Alloys and Compounds**, 495, 280-283.
- [87] Kantha, P., Pengpat, K., Jarupoom, P., Intatha, U., Rujijanagul, G. and Tunkasiri, T. (2009). Phase formation and electrical properties of BNLT-BZT lead-free piezoelectric ceramic system. **Current Applied Physics**, 9, 460-466.
- [88] Sumang, R., Vittayakorn, N. and Bongkarn, T. (2013). Crystal structure, microstructure and electrical properties of  $(1-x-y)Bi_{0.5}Na_{0.5}TiO_3-xBi_{0.5}K_{0.5}TiO_3-yBiFeO_3$  ceramics near MPB prepared via the combustion technique. **Ceramics International**, 39 (1), S409-S413.
- [89] Razak, K. A., Yip, C. J. and Sreekantan, S. (2011). Synthesis of  $(Bi_{0.5}Na_{0.5})TiO_3$  (BNT) and Pr doped BNT using the soft combustion technique and its properties. **Journal of Alloys and Compounds**, 509, 2936-2941

- [90] Julphunthong, P., Chootin, S. and Bongkarn, T. (2013). Phase formation and electrical properties of  $\text{Ba}(\text{Zr}_x\text{Ti}_{1-x})\text{O}_3$  ceramics synthesized through a novel combustion technique. **Ceramics International**, 39, S415-S419.
- [91] Tian, Y., Wei, L., Chao, X., Liu, Z. and Yang, Z. (2013). Phase transition behavior and large piezoelectricity near the morphotropic phase boundary of lead-free  $(\text{Ba}_{0.85}\text{Ca}_{0.15})(\text{Zr}_{0.1}\text{Ti}_{0.9})\text{O}_3$  Ceramics. **J. Am. Ceram. Soc.**, 96, 496–502.
- [92] Shieh, J., Wu, K. C. and Chen, C. S. (2007). Switching characteristics of MPB compositions of  $(\text{Bi}_{0.5}\text{Na}_{0.5})\text{TiO}_3$ – $\text{BaTiO}_3$ – $(\text{Bi}_{0.5}\text{K}_{0.5})\text{TiO}_3$  lead-free ferroelectric ceramics. **Acta Materialia**, 55, 3081-3087.

